

IFP-300ECS / IFP-300ECSB

Emergency Communication System with Fire Alarm Control Panel

The IFP-300ECS (red) and IFP-300ECSB (black) are Intelligent analog/addressable fire alarm control panels (FACP) combined with an Emergency Communication System (ECS). When the ECS features are enabled, they are integrated with the fire alarm and voice evacuation functions of the control panel. The IFP-300ECS panel and accessories provide features to meet the requirements for Mass Notification Systems as described in UL 2572.

This state of the art fire alarm control panel allows you to choose one of three SLC protocols per system. The basic IFP-300ECS panel contains one built in signaling line circuit (SLC), which can support 159 System Sensor® IDP/SK sensors and 159 IDP/SK modules or 127 (SD) Hochiki® devices per loop. Additional SLC loops can be added using the model 6815 SLC expander for IDP/SK devices to increase the overall point capacity to a maximum of 300 points per panel, or model 5815XL SLC Expander for SD devices to increase the overall point capacity to a maximum of 254 points per panel.

IFP-300ECS has the interconnection capability for up to 32 panels. The system has two modes of operation, multiple panels covering one larger building, or multiple independent buildings. A separate network can be used for voice paging across all panels.

The IFP-300ECS supports a variety of devices, including RA- 2000, RA-1000 or RA-100 remote annunciator, 5824 serial parallel printer interface module (for printing system reports), RPS-1000 power module, and IDP, SK or SD devices.



IFP-300ECSB

Compatibility

The IFP-300ECS is compatible with the following ECS components:

- ECS-50W, ECS-125W, ECS-INT50W or ECS-DUAL50W Amplifier
- ECS-RVM: Remote voice module
- ECS-SW24: 24 switch expander (max 2)
- ECS-NVCM: Network Voice Control Module (included)

FEATURES & BENEFITS

- Single enclosure for both Fire and Emergency Control System components
- Can select ECS message as priority over fire
- Built-in support for up to 159 IDP/SK detectors and 159 IDP/SK modules or 127 SD SLC devices
- Four line LCD display with 40 characters per line
- On-board supervised microphone
- Available in a red or black cabinet
- Separate network support for voice paging
- Built-in USB interface for programming
- Built-in dual phone line, digital alarm communicator/transmitter (DACT), IP or optional cellular technologies
- JumpStart AutoProgramming® feature for easy programming
- Capable of producing 520 Hz tones to meet NFPA 72 requirements
- 15 Recordable one minute messages that can be mapped to eight ECS buttons
- Firmware can be upgraded in the field
- Supports up to four SWIFT wireless gateways. Each gateway can have up to 49 wireless devices
- Support for up to eight SBUS addressable amplifiers using a combination of ECS-50W, ECS-125W, ECS-INT50W or ECS-DUAL50W for a maximum of 1000 watts per system
- Supports up to seven ECS-LOC's
- Network support for up to 32 Sites

IFP-300ECS Technical Specifications

PHYSICAL

Overall Dimensions: 21.59"W x 28.10"H x 5.05"D

Shipping Weight: 49 lbs.

Color: Red or Black

ENVIRONMENTAL

Operating Temperature: 32°F to 120°F (0°C to 49°C)

Humidity: 0 to 93% relative humidity (non-condensing)

ELECTRICAL:

IFP-300ECS Primary AC: 120 VAC @ 60 Hz, 3.6A
Total Accessory Load: 6A @ 24 VDC power-limited

Standby Current: 190 mA

Alarm Current: 250mA

Battery Charging Capacity: 17 to 55AH

Battery Size: 18AH max. allowed in control panel cabinet. Larger capacity batteries can be housed in RBB accessory cabinet.

APPROVALS

NFPA 13, NFPA 15, NFPA 16, NFPA 70, & NFPA 72: Central Station; Remote Signalling; Local Protective Signalling Systems; Auxiliary Protected Premises Unit; & Water Deluge Releasing Service

- **UL Listing**
- **CSFM:** 7165-0559:0504
- **FNDY:** COA# 6245
- **Seismic (CA)** (pending)
- **FM approved**

COMPATIBLE DEVICES

See the data sheets listed below for a complete listing of the IDP, SK, SWIFT or SD devices.

350361: IDP Device Protocol data sheet

53623: SK Device Protocol data sheet

350360: SD Device Protocol data sheet

350615 & 350617: SWIFT devices data sheet

ORDERING INFORMATION

IFP-300ECS: Emergency Communication System with FACP. Red Cabinet.

IFP-300ECSB: Emergency Communication System with FACP. Black Cabinet.

ECS ACCESSORIES

ECS-50W: 50 Watt Amplifier

ECS-125W: 125 Watt Amplifier

ECS-DUAL50W: 50 Watt Dual Amplifier

ECS-DUAL50WB: 50 Watt Dual Amplifier, Black

ECS-50WB: 50 Watt Amplifier, Black

ECS-125WB: 125 Watt Amplifier, Black

ECS-INT50W: 50 /Watt Internal Amplifier

ECS-50WBU: External Backup Amplifier

ECS-CE4: Provides 4 additional audio circuits

ECS-RVM: Remote voice module

ECS-SW24: 24 Switch Expander

ECS-NVCM: Network Voice Control Module

ECS-LOC: Local Operator Console

SBUS ACCESSORIES

RA-2000, RA-1000, RA-1000R, RA-100,

RA-2000GRAY: Remote annunciators

6815: Signal Line Circuit (SLC) Expander for IDP or SK devices

5815XL: Signal Line Circuit (SLC) Expander for SD devices

RPS-1000: Power Supply

5496: NAC Expander

5824: Serial/Parallel Module

5880: LED I/O Module

5865-3 or 5865-4: LED Annunciator

5883: Relay Interface

MISCELLANEOUS ACCESSORIES

HFSS: Software Suite. Provides programming, upload/download and event reporting

RBB: Remote Battery Box Cabinet. Use for backup batteries up to 35AH. Dimensions: 16"W x 10"H x 6"D

SK-SCK: Seismic Compliance Kit

SK-NIC: Network Interface Card

SK-NIC-KIT: Installation Accessory Kit

SK-FML: Fiber-Optic Multi Mode, transmitter and receiver

SK-FSL: Fiber-Optic Single Mode

CELL-MOD: Cellular Communicator in Plastic Enclosure

CELL-CAB-SK: Cellular Communicator in Metal Enclosure with lock and key

For a complete listing of all compliance approvals and certifications, please visit www.farenhyt.com.

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

SWIFT® and Honeywell® are registered trademarks of and Farenhyt™ is a trademark of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, Please call 800-446-6444.

For more information

Learn more about Honeywell Farenhyt Series products available by visiting www.farenhyt.com

Honeywell Farenhyt

12 Clintonville Road
Northford, CT 06472
800-328-0103